

## stainless steel high pressure filters



### a comprehensive range of stainless steel filters ideal for a wide variety of high pressure applications

The nano F<sup>4</sup> range of stainless steel high pressure filters consists of 21 models across three pressure ranges offering flow ratings up to 2000 scfm and pressure ratings up to 5000 psig.

Manufactured from high grade 316 stainless steel the nano F<sup>4</sup> range is precision engineered with high pressure applications in mind.

The 725 psig range incorporates an innovative push-fit element design to ensure optimum sealing and mechanical strength. Elements are color coded for easy identification. The 1450 and 5000 psig ranges incorporate elements with corrosion resistant stainless steel end caps.

### up to 5000 psig MAWP

Wide selection of filtration grades as well as a water separator option. Filtration grades include M25, M1, M01 and AC which provide a solution for the most demanding applications. The custom engineered filter media is designed to provide low air velocity preventing oil carry over for high efficiency filtration with minimal pressure drop.

Manufactured in an ISO 9001 approved facility and tested in accordance with ISO 8573-1:2010.



#### applications include:

chemical

food & beverage

manufacturing

military

oil & gas

pharmaceuticals

**nano-purification solutions llc**  
charlotte, north carolina  
united states


**nano-purification solutions**  
st. catharines, ontario  
canada

**nano-purification solutions ltd**  
gateshead, tyne and wear  
united kingdom

tel: 704.897.2182  
fax: 704.897.2183  
email: support@n-psi.com  
web: www.n-psi.com

# technical specification

filter model	inlet & outlet	maximum rated flow <sup>(1)</sup>		dimensions (inches)				approximate weight	replacement element
	NPT	scfm	Nm³/h	A	B	C	D	lbs	
N50SS (725 psig)									
N50SS 0060 (grade)	¼"	60	100	3.34	0.70	6.69	2.95	3.7	E50SS 0060 (grade)
N50SS 0120 (grade)	⅜"	120	200	3.34	0.70	8.07	3.93	4.4	E50SS 0120 (grade)
N50SS 0200 (grade)	½"	200	340	3.34	0.70	8.07	3.93	4.8	E50SS 0200 (grade)
N50SS 0300 (grade)	¾"	300	500	4.43	1.06	10.6	5.90	8.8	E50SS 0300 (grade)
N50SS 0600 (grade)	1"	600	1000	4.43	1.06	16.5	11.8	11.0	E50SS 0600 (grade)
N50SS 1000 (grade)	1½"	1000	1700	5.90	1.77	20.7	11.8	33.0	E50SS 1200 (grade)
N50SS 1200 (grade)	2"	1200	2040	5.90	1.77	20.7	11.8	33.0	E50SS 1200 (grade)
N50SS 2000 (grade)	2"	2000	3400	5.90	1.77	32.5	19.7	46.2	E50SS 2000 (grade)
N100SS (1450 psig)									
N100SS 0060 (grade)	¼"	60	100	2.55	0.78	5.31	2.75	7.0	E100SS 0060 (grade)
N100SS 0185 (grade)	½"	185	315	2.55	0.78	9.84	7.08	12.3	E100SS 0185 (grade)
N100SS 0270 (grade)	¾"	270	460	3.46	0.78	10.8	9.84	13.4	E100SS 0270 (grade)
N100SS 0400 (grade)	1"	400	680	5.19	1.02	10.4	9.84	23.1	E100SS 0400 (grade)
N100SS 0700 (grade)	1"	700	1200	5.19	1.02	18.9	11.8	32.4	E100SS 0700 (grade)
N100SS 1000 (grade)	1½"	1000	1700	5.90	1.77	20.7	11.8	48.5	E100SS 1000 (grade)
N100SS 2000 (grade)	2"	2000	3400	5.90	1.77	32.5	19.7	61.7	E100SS 2000 (grade)
N350SS (5000 psig)									
N350SS 0028 (grade)	¼"	28	48	1.61	0.39	4.05	2.36	3.5	E350SS 0028 (grade)
N350SS 0067 (grade)	¼"	67	111	2.55	0.78	5.31	2.75	7.0	E350SS 0067 (grade)
N350SS 0150 (grade)	½"	150	255	2.55	0.78	8.26	5.90	12.3	E350SS 0150 (grade)
N350SS 0300 (grade)	¾"	300	510	3.46	0.98	11.0	9.84	13.4	E350SS 0300 (grade)
N350SS 0445 (grade)	1"	445	750	5.90	1.37	13.0	7.87	31.5	E350SS 0445 (grade)
N350SS0775 (grade)	1"	775	1330	5.90	1.37	18.9	11.8	38.3	E350SS 0775 (grade)



element performance	WS <sup>(2)</sup>	M25	M5	M1	M01	AC
particle removal (microns)	-	25	5	1	0.01	-
max oil carry over at 68°F (ppm or mg/m <sup>3</sup> )	25	10	5	0.1	0.01	0.003
recommended operating temp range (°F)	35-212	35-212	35-212	35-212	35-212	35-77
design operating temperature range (°F)	36-248	35-248	35-248	35-248	35-248	35-122

specifications	N50SS	N100SS	N350SS
design operating pressure range (psig)	0 to 725	0 to 1450	0 to 5000
condensate drain (included)		manual ball valve	
housing material		316 stainless steel	

pressure correction factors									
N50SS (725 psig)									
operating pressure (psig)	60	90	120	150	220	290	435	580	725
correction factor	0.14	0.22	0.28	0.34	0.47	0.56	0.70	0.85	1.00
N100SS (1450 psig)									
operating pressure (psig)	290	435	580	725	870	1015	1160	1305	1450
correction factor	0.45	0.57	0.68	0.80	0.84	0.88	0.92	0.96	1.00
N350SS (5000 psig)									
operating pressure (psig)	725	1450	2175	2900	3625	4350	5000	-	-
correction factor	0.73	0.78	0.82	0.87	0.91	0.96	1.00	-	-

(1) at 725, 1450 or 5000 psig as applicable. For all other pressures, refer to the pressure correction factor table above

(2) not available for models N50SS 0060, N50SS 2000, N100SS 0700, N100SS 1000, N350SS 0150, N350SS 0300, N350SS 0445 and N350SS 0775

- install with air flow inside to outside for coalescing filtration and outside to inside for dry particulate filtration
- differential pressure indicator not included